| <b>BIG BIKE PARTS</b> <sup>®</sup>  |                            | INSTALLATION INSTRUCTIONS  |  |    |
|---|----------------------------|--|--|----|
| Copyright <sup>©</sup> 2019 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written |                            | PART NO. 21-358BK  | BLACK COMMANDER HWY BOARD  | )S |
| permission of Big Bik   | e Parts, Inc.              | FITMENT: HONDA GO  | OLDWING/GOLDWING TOUR 2018-NEWER   |    |
| 5/23/2019<br>TOOLS NEEDED:  | 6MM ALLEN WRENCH           |  | 1 ALLEN WRENCH 8MM ALLEN WRENCH REMOVABLE THREAD LOC   | ~ĸ |
|   |                            |  | 5. *USE REMOVABLE THREAD LOCK ON ALL FASTENERS*  |    |
| ESTIMATED INST  | ALLATION TIME: 45 TO 60 MI | Ν.   |  |    |
| INSTALLATION:   |                            |  |  | _  |
| 1   |                            |  | REWS IN FIG. 1. PULL FORWARD ON THE LEFT FOG LIGHT COVER TO REMOVE IT  | •  |
| 2   |                            | ICH TO REMOVE THE TWO ALLEN SCREWS<br>THE REAR OF THE LEFT LOWER COWL TO |  |    |
| 4   |                            |  | IE LEFT LOWER COWL TAB FROM THE LOWER SHROUD.  |    |
| - 5   |                            | OMMET IN THE CENTER OF THE LEFT LOV                                      |  |    |
| 6   | SUIGHTLY PULL OUT ON T     | THE BACK AND BOTTOM OF THE LEFT LOW                                      | WER COWL AND SLIDE IT FORWARD AND OUT TO RELEASE THE TAB HOLDING T<br>IND PLACE IT ON A CLEAN TOWEL OR SOFT SURFACE TO AVOID SCRATCHING.   | ΉE |
| 7   | REMOVE THE TWO CLIPS       | FROM THE ENGINE GUARD COVER (FIG. 5                                      | 5 SHOWS INSIDE OF THE LEFT LOWER COWL) CLIPS WILL NOT BE REUSED.   |    |
| 8   | . PRESS THE THREE TABS IN  | NSIDE THE LOWER COWL TO RELEASE THE                                      | EM AND REMOVE THE ENGINE GUARD COVER. COVER WILL NOT BE REUSED.  |    |
| 9   | PLACE ONE OF THE CLAM      | IP TOPS ON THE ENGINE GUARD AS SHOW                                      | WN IN FIG. 6.  |    |
| 1   | 0. REPEAT STEPS 1 THROUG   | H 6 IN REVERSE ORDER.  |  |    |
| _   | FORWARD OR BACK SLIGI      | HTLY TO ADJUST POSITION/ANGLE OF THE                                     | T COMMANDER HIGHWAY BOARD. (DO NOT TIGHTEN. <i>CLAMP CAN MOVE<br/>IE BOARD</i> ) ONCE IT IS IN PLACE, TIGHTEN ALL BOLTS AND THE SET SCREW. |    |
| 1   | 2. REPEAT ON THE RIGHT SI  | DE.  |  |    |
| TV  | NOVE<br>NO<br>EEWS         | LEFT FOG<br>LIGHT<br>COVER   | RELEASE<br>REMOVE<br>TWO 5MM<br>ALLEN<br>SCREWS<br>FIG. 2  |    |
| 100000  |                            |  | PULL STRAIGHT<br>BROMMET   |    |
| FIG   | i. 3                       | LEFT<br>EXHAUST<br>HEAT SHIELD   | FIG. 4   |    |

