



Goldstrike Taillight Trim

Parts Included:

- 1 Left side taillight trim
- 1 Right side taillight trim

Installation Instructions:

1. Park on a level surface and shut off the motorcycle. Ensure that the engine has time to cool before installation.

Note: Ideal installation temperatures are between 70°F to 100°F (21°C to 38°C). The minimum suggestion application temperature is 50°F (10°C).

2. Determine left and right side parts by dry fitting into place.

3. Take note of final position, it may be helpful to use masking tape to mark the final location.

4. Clean motorcycle with an ammonia based glass cleaner. Be sure all oils & waxes are removed and the area is dry and lint-free.

5. Remove tape liner and press parts into place with firm pressure, holding for 30 seconds. Bond strength will increase over time; approximately 50% of ultimate bond strength will be achieved after 20 minutes, 90% after 24 hours and 100% after 72 hours. Be most cautious during this time.



WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION:

This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LED failure.

Ciro will have no obligation if the customer cannot show proof of purchase. Warranty will not be granted unless the part is properly installed and maintained. Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products.

Please visit our website Ciro3d.com for our complete warranty policy.