

# SLA

FACTORY ACTIVATED

SLA | READY TO START

# REF BTX20HL



**12V** VOLTAGE - V

**310A** CCA - A

**18.9Ah** CAPACITY - Ah (20Hr)

**18Ah** CAPACITY - Ah (10Hr)

## TECHNOLOGY

- Designed according to AGM technology (Absorbed acid)
- VRLA battery type
- Activated and pre-charged batteries
- Homologated by OEM

## FEATURES

- AGM construction (Absorbed Glass Material)
- VRLA battery (Valve Regulated Lead Acid)
- Factory activated
- Environmentally friendly, spillproof design
- Multi-positional fitment
- Absolutely Maintenance free
- Sealed, no gas emission through venting hole (under normal operation)
- Ready & Easy to use
- No acid handling - Very safe
- Increased power & Extended life
- Extreme vibration resistance


## UPGRADE FOR

BTX20HL-BS

## WEIGHT


Battery (with acid) : Approx 6.04kg (13.30lbs)

## MOUNTING ANGLE



## DIMENSIONS

Length (A) : 175±2mm (6.89 in)  
 Width (B) : 87±2mm (3.43 in)  
 Container height : 155±2mm (6.10 in)  
 Total height (C) : 155±2mm (6.10 in)



## TERMINALS

